

Sugarcane Planter



جان بھی اور ڈائیر بھی



Most productive 800 – 1,000 kg of sugarcane can be loaded into planter basket to deliver higher performance and costs less to operate in terms of fuel consumption and laborious.

Most accurate Mechanical planting enable uniform row spacing which will improve efficiency of mechanical harvesters and result in higher percentage of germination.

Easy to adjust The depth is easy to control and can be adjusted to 6 levels based on soil type to get more even emergence and more uniform stands.

High Quality Parts The structure and major components are more durable with high quality of material.



Technical Specification



JOHN DEERE

| Model | SP3030 | SP3040 | SP3130 | SP3140 |
|-------------------------------|---------------------------|---------------------------|--|--|
| Tractor Power (hp.) | 55-65 | 55-65 | 65-117 | 65-117 |
| Tractor Compatibility | 5310E/5055E/5065E | 5310E/5055E/5065E | 5065E/5610E/5075E/5715/5090E/6100B/6110B | 5065E/5610E/5075E/5715/5090E/6100B/6110B |
| Type | Double row | Double row | Double row | Double row |
| Billet spacing (mm) | 300 | 400 | 300 | 400 |
| Billet Capacity (kg) | 800* | 800* | 1000* | 1000* |
| Working Depth (mm) | 100-300 | 100-300 | 100-300 | 100-300 |
| 3 Point Hitch | CATII | CATII | CATII | CATII |
| Fertilizer tank capacity (kg) | 50 | 50 | 50 | 50 |
| Roller | Options: Single/Double | Options: Single/Double | Options: Single/Double | Options: Single/Double |
| Dimension | | | | |
| Overall Width (mm) | 1,600 | 1,600 | 2,000 | 2,000 |
| Overall height (mm) | 2,100 | 2,100 | 2,400 | 2,400 |
| Weight (kg) | 740 | 740 | 880 | 880 |
| Basket Height (mm) | 1,200 | 1,200 | 1,400 | 1,400 |

* For maximize the efficiency – Tractor with Hydraulic Cylinder Assistant is recommended.

Official Dealer



Farm Dynamics Pakistan (Pvt) Ltd

7-J1, Canal Bank, Johar Town, Lahore. Tel: +92 42 35312301 Web: www.fdp.com.pk